

# HS30

## High Speed Rotary Sheeter



HP Indigo  
Business Partner

• *Designed for HP Indigo*



SPECIFICATIONS	METRIC	IMPERIAL
Web width	254 - 762 mm	10 - 30"
Substrate thickness	80 - 500 gsm	
<b>Die Station full rotary</b>		
Speed	60 m/min	197 ft/min
"Repeat range	508 - 1016 mm	20 - 40"
<b>Unwinder</b>		
Diameter max.	800 mm	31.5"
Max roll weight	700 kg	1543 lbs
Core diameter	76,2 mm	3"
<b>Rewinder</b>		
Diameter max.	400 mm	15.7"
Core diameter	76,2 mm	3"
<b>Flexo Station Option</b>		
Varnishing roller	Ø97.2mm / SH65	
Spot varnish repeat plate cylinder (optional)	305 - 482,6 mm	12 - 19"
<b>Slitting Station Option</b>		
Knife type	Pneumatic crush or razor	
Minimum distance	12,7 mm	0.5"
<b>Dimensions (WxDxH)</b>	4,8x1,9x1,7 m	15.7x6.2x5.6 ft

The **HS30** rotary sheeter is a cut-to-mark high-speed sheeter for 30" wide web. It is designed to convert roll-fed material into sheets. The size can be from 20" to 40" depending on tooling. A precision register is managed by servo drive technology. The HS30 can deliver sheets to a conveyor or a stacker solution. The unwind station is a double-sided hydraulic unwind stand with tension control and lift from floor function. Maximum diameter is 800 mm. The **HS30** is designed for easy integration with digital presses. Optional flexo coating unit is available.