

GR80



SPECIFICATIONS	METRIC	IMPERIAL
Max. trim width	30 mm	1.2"
Max. trim extraction speed	200 m/min	656 ft/min
Connection tube diameter inlet int/ext dimensions	63/75 mm	2.5/3"
Dimensions (WxDxH)	0,6 x 0,5 x 1,1 m	2 x 1.7 x 3.6 ft
Weight	45 kg	99 lbs
Power supply	3 x 230/400 V AC, 50/60 Hz	

GR80

Shredder is specially designed for use with printing presses or slitters already provided with waste removal equipment. It can efficiently shred a wide range of label materials and reduce them to a few percentages of the original volume. The **GR80** trim shredder is mounted in a stand the height of which is adjustable up to max. 110 cm (43.3") above the floor.

GR80K



SPECIFICATIONS	METRIC	IMPERIAL
Max. trim width	30 mm	1.2"
Max. trim extraction speed	200 m/min	656 ft/min
Connection tube diameter inlet int/ext dimensions	2x63 / 1x90 mm	2x2.5" / 1x3.5"
Dimensions (LxWxH)	0,95 x 0,86 x 1,3 m	3.1 x 2.8 x 4.2 ft
Weight	100 kg	220 lbs
Power supply	200-240V AC+PE, 50/60 Hz, 16A *208-240VAC (2P+ PE) for US	

GR80K

The GR80K combines a shredder with a built-in waste removal unit with heavy suction power. Designed to shred a wide range of material and reduce it to approx. 5 - 10 % of the original volume. The GR80K shredder has connections for two machines. The Waste Bag System allows the use of canvas bags for shredded material. An optional lubrication system can be added to both GR80 and **GR80K** to use for materials with adhesive to prevent glue buildup on the knives.

SU3



SPECIFICATIONS	METRIC	IMPERIAL
Max. trim width	35 mm	1.4"
Max. trim extraction speed	150 - 200 m/min	492 - 656 ft/min
Dimensions (LxWxH)	0,6 x 0,4 x 0,6 m	2 x 1.3 x 2 ft
Weight	35 kg	77 lbs
Power supply	3 x 230/400 V AC, 50/60 Hz	

SU3 - Waste Removal Unit

The SU3 is an inline shredder for slitting applications, designed to convey trim from slitters of almost any make to a waste bin. The SU3 is mounted on wheels and is easily moved from one machine to another. The standard equipment comprises a noiseless ventilator enclosed in a noise absorbing cabinet. Height adjustment of the suction nozzle ranges from 1,0-1,5 m (3.3-4.9 ft) and the maximum distance from the suction nozzle to the trim knives is 0,25 - 0,5 m (9.8 - 19.7"), subject to the material and thickness.